

SSG-100S



GENERAL DESCRIPTION

Optima sliding speed gates provide aesthetic and effective control of entry or exit at kinds of toll collection systems like train/metro stations, and access control for commercial centers, stadiums, schools, government and private sector buildings etc.

SYSTEM SPECIFICATIONS

- ⇒ Main body and lateral lids are AISI 304-grade stainless steel.
- ⇒ Top cover and flaps are tempered glass.
- ⇒ Lateral covers are removable for easy maintenance.
- ⇒ Motor start and stop control is maintained by Optima PLC controller.
- ⇒ Low power consumption and silent running.
- ⇒ Compatible with all access control systems.
- ⇒ Turnstile is equipped with an alarm system which senses forbidden and reverse direction passing.
- ⇒ Turnstiles closes flaps by itself after adjusted time if a valid card is presented but person not passed.
- ⇒ All the obstacles in the passage are sensed with photoelectric sensors.
- ⇒ Indoor use only.

ENVIRONMENTAL CONDITIONS AND POWER REQUIREMENT

Between -15°C and +65°C, 95% non-condensing humidity; 220-240 VAC, mono phase, 50-60 Hz.

OPTIONAL ACCESSORIES

- ▶ Push button box.
- ▶ Logo print on the flaps.
- ▶ Card reader system.
- ▶ Digital Counter.
- ▶ Card reader mounting plate inside or on the turnstile.
- ▶ Card reader mounting plate with pedestal.
- ▶ Stainless steel railing.
- ▶ Uninterrupted power supply (UPS)
- ▶ SCADA or any control system: It is turnstile to change and check the position of the turnstile with a touch screen control panel, mobile devices (ios-android), computer, etc.

MAIN BODY MEASUREMENTS

